

Proposed Code Change State Form 41186R

RETURN TO: INDIANA DEPARTMENT OF HOMELAND SECURITY CODE SERVICES SECTION 302 W. Washington Street Room W246

Indianapolis, IN 46204

INSTRUCTIONS:

Only TYPED copy accepted.

(KEY - Dashed line through material to be deleted, underline material to be added)

FOR OFFICE USE ONLY

Received 5/12/09

Code 48-09R

Use second sheet for any material requiring more space.		
Code Title		Edition
International Residential Code		2009
Section number and title		Page
R401.3 Drainage, Exception Revised		71
Proponent	Title	
Carolyn Schleif President, Nightingale		Designs, Inc.
Address		Phone
10517 Hyde Park, Carmel, IN 46032		(317) 580-0540
PROPOSED CODE CHANGE (Check One)		
Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution R401.3 Drainage. Surface drainage shall be diverted to a storm sewer conveyance or other approved point of collection that does not create a hazard. Lots shall be graded to drain surface water away from foundation walls. The grade shall fall a minimum of 6 inches (152 mm) within the first 10 feet (3048 mm). Exception: Where lot lines, walls, slopes or other physical barriers prohibit 6 inches (152 mm) of fall within 10 feet (3048 mm), drains or swales shall be constructed to ensure drainage away from the structure of equivalent cross-sectional area to that listed in R401.3. Impervious surfaces within 10 feet (3048 mm) of the building foundation shall be sloped a minimum of 2 percent away from the building.		
REASON AND FISCAL IMPACT		
Reason: This would prevent water accumulation and mold between residences. The same amount of water is shed from roofs no matter how close they are. Fiscal impact: None, this can be done during construction or grading.		
REVIEW RECOMMENDATION		
Approve		
Disapprove		
Approve as amended		
Further Study		